

Package: PrettyCols (via r-universe)

October 10, 2026

Title Pretty Colour Palettes

Version 1.1.0.9003

Description Defines aesthetically pleasing colour palettes.

License CC0

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Depends R (>= 3.6)

Imports ggplot2, graphics, grDevices, lifecycle

Suggests covr, jsonlite, knitr, markdown, purrr, rmarkdown, testthat
(>= 3.0.0)

Config/Needs/website nrennie/nrenniepkgdown

URL <https://nrennie.rbind.io/PrettyCols/>,
<https://github.com/nrennie/PrettyCols>

BugReports <https://github.com/nrennie/PrettyCols/issues>

VignetteBuilder knitr

Config/testthat/edition 3

Repository <https://nrennie.r-universe.dev>

Date/Publication 2025-04-23 01:04:00 UTC

RemoteUrl <https://github.com/nrennie/prettycols>

RemoteRef HEAD

RemoteSha d754b34d2e08dc9b85494c59cc99421ce5ef0651

Contents

colorblind_friendly	2
colourblind_friendly	3
prettycols	3

PrettyColsPalettes	4
scale_color_pretty_c	4
scale_color_pretty_d	5
scale_color_pretty_div	6
scale_colour_pretty_c	6
scale_colour_pretty_d	7
scale_colour_pretty_div	8
scale_fill_pretty_c	8
scale_fill_pretty_d	9
scale_fill_pretty_div	10
view_all_palettes	10
Index	12

colorblind_friendly	Returns a data frame of colorblind friendly colour palettes
---------------------	---

Description

Returns a data frame of colorblind friendly colour palettes

Usage

```
colorblind_friendly(palettes = PrettyColsPalettes)
```

Arguments

palettes List of palettes. Default PrettyColsPalettes.

Value

A data frame with two columns giving names and types of colourblind friendly palettes.

Examples

```
colorblind_friendly()
```

colourblind_friendly	<i>Returns a data frame of colourblind friendly colour palettes</i>
----------------------	---

Description

Returns a data frame of colourblind friendly colour palettes

Usage

```
colourblind_friendly(palettes = PrettyColsPalettes)
```

Arguments

palettes List of palettes. Default PrettyColsPalettes.

Value

A data frame with two columns giving names and types of colourblind friendly palettes.

Examples

```
colourblind_friendly()
```

prettycols	<i>Generates the colour palettes</i>
------------	--------------------------------------

Description

Generates the colour palettes

Usage

```
prettycols(palette, n, type = "discrete", direction = 1)
```

Arguments

palette	Name of Palette. Run names(PrettyColsPalettes) to view options.
n	Number of desired colors. If number of requested colors is beyond the scope of the palette, colors are automatically interpolated. If n is not provided, the length of the palette is used.
type	Either "continuous" or "discrete". Use continuous if you want to automatically interpolate between colors. Default "discrete"
direction	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed

Value

A character vector of hex colour codes.

Examples

```
prettycols("Blues")
```

PrettyColsPalettes	<i>Complete list of palettes.</i>
--------------------	-----------------------------------

Description

Use names(PrettyColsPalettes) to return all palette names.

Usage

```
PrettyColsPalettes
```

Format

An object of class list of length 46.

scale_color_pretty_c	<i>Plotting with PrettyCols palettes for colour ggplot2</i>
----------------------	---

Description

Plotting with PrettyCols palettes for colour ggplot2

Usage

```
scale_color_pretty_c(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

palette	Name of Palette. Run names(PrettyColsPalettes) to view options.
direction	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
legend_title	[Deprecated] Deprecated in favour of name.
...	Other arguments passed on to scale_color_gradientn

Value

A ggproto object defining a continuous colour scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, color = wt)) +
  geom_point() +
  scale_color_pretty_c("Greens")
```

scale_color_pretty_d *Plotting with PrettyCols palettes for colour ggplot2*

Description

Plotting with PrettyCols palettes for colour ggplot2

Usage

```
scale_color_pretty_d(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

palette	Name of Palette. Run <code>names(PrettyColsPalettes)</code> to view options.
direction	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
legend_title	[Deprecated] Deprecated in favour of name.
...	Other arguments passed on to discrete_scale

Value

A ggproto object defining a discrete colour scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, color = factor(cyl))) +
  geom_point() +
  scale_color_pretty_d("Bright")
```

`scale_color_pretty_div`*Plotting with PrettyCols palettes for colour ggplot2*

Description

Plotting with PrettyCols palettes for colour ggplot2

Usage

```
scale_color_pretty_div(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

<code>palette</code>	Name of Palette. Run <code>view_all_palettes(type = "div")</code> to view options. Must be a diverging palette name.
<code>direction</code>	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
<code>legend_title</code>	[Deprecated] Deprecated in favour of name.
<code>...</code>	Other arguments passed on to scale_colour_gradient2

Value

A ggproto object defining a continuous colour scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, colour = wt)) +
  geom_point() +
  scale_color_pretty_div("PurpleYellows", midpoint = mean(mtcars$wt))
```

`scale_colour_pretty_c` *Plotting with PrettyCols palettes for colour ggplot2*

Description

Plotting with PrettyCols palettes for colour ggplot2

Usage

```
scale_colour_pretty_c(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

palette	Name of Palette. Run names(PrettyColsPalettes) to view options.
direction	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
legend_title	[Deprecated] Deprecated in favour of name.
...	Other arguments passed on to scale_colour_gradientn

Value

A ggproto object defining a continuous colour scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, colour = wt)) +
  geom_point() +
  scale_colour_pretty_c("Greens")
```

scale_colour_pretty_d *Plotting with PrettyCols palettes for colour ggplot2*

Description

Plotting with PrettyCols palettes for colour ggplot2

Usage

```
scale_colour_pretty_d(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

palette	Name of Palette. Run names(PrettyColsPalettes) to view options.
direction	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
legend_title	[Deprecated] Deprecated in favour of name.
...	Other arguments passed on to discrete_scale

Value

A ggproto object defining a discrete colour scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, colour = factor(cyl))) +
  geom_point() +
  scale_colour_pretty_d("Bright")
```

scale_colour_pretty_div

Plotting with PrettyCols palettes for colour ggplot2

Description

Plotting with PrettyCols palettes for colour ggplot2

Usage

```
scale_colour_pretty_div(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

palette	Name of Palette. Run <code>view_all_palettes(type = "div")</code> to view options. Must be a diverging palette name.
direction	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
legend_title	[Deprecated] Deprecated in favour of name.
...	Other arguments passed on to scale_colour_gradient2

Value

A ggproto object defining a continuous colour scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, colour = wt)) +
  geom_point() +
  scale_colour_pretty_div("PurpleYellows", midpoint = mean(mtcars$wt))
```

scale_fill_pretty_c

Plotting with PrettyCols palettes for colour ggplot2

Description

Plotting with PrettyCols palettes for colour ggplot2

Usage

```
scale_fill_pretty_c(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

palette	Name of Palette. Run names(PrettyColsPalettes) to view options.
direction	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
legend_title	[Deprecated] Deprecated in favour of name.
...	Other arguments passed on to scale_fill_gradientn

Value

A ggproto object defining a continuous fill scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, fill = wt)) +
  geom_point(pch = 21) +
  scale_fill_pretty_c("Greens")
```

scale_fill_pretty_d *Plotting with PrettyCols palettes for colour ggplot2*

Description

Plotting with PrettyCols palettes for colour ggplot2

Usage

```
scale_fill_pretty_d(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

palette	Name of Palette. Run names(PrettyColsPalettes) to view options.
direction	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
legend_title	[Deprecated] Deprecated in favour of name.
...	Other arguments passed on to discrete_scale

Value

A ggproto object defining a discrete fill scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, fill = factor(cyl))) +
  geom_point(pch = 21) +
  scale_fill_pretty_d("Bright")
```

`scale_fill_pretty_div` *Plotting with PrettyCols palettes for fill colour ggplot2*

Description

Plotting with PrettyCols palettes for fill colour ggplot2

Usage

```
scale_fill_pretty_div(palette, direction = 1, legend_title = NULL, ...)
```

Arguments

<code>palette</code>	Name of Palette. Run <code>view_all_palettes(type = "div")</code> to view options. Must be a diverging palette name.
<code>direction</code>	Sets order of colors. Default palette is 1. If direction is -1, palette color order is reversed
<code>legend_title</code>	[Deprecated] Deprecated in favour of name.
<code>...</code>	Other arguments passed on to scale_colour_gradient2

Value

A ggproto object defining a continuous colour scale for use with ggplot2.

Examples

```
library(ggplot2)
ggplot(data = mtcars, aes(x = mpg, y = disp, fill = wt)) +
  geom_point(pch = 21) +
  scale_fill_pretty_div("PurpleYellows", midpoint = mean(mtcars$wt))
```

`view_all_palettes` *Prints all available colour palettes*

Description

Prints all available colour palettes

Usage

```
view_all_palettes(type = "all", colourblind_friendly = FALSE)
```

Arguments

- `type` Type of colour palettes to view. Either all palettes, sequential palettes, diverging palettes, or qualitative palettes. Types must be at least one of `c("all", "seq", "div", "qual")`. Default "all".
- `colourblind_friendly` Boolean whether or not to return only colourblind friendly palettes. Default FALSE.

Value

A plot of all colour palettes available in the package.

Examples

```
view_all_palettes(type = "seq")
view_all_palettes(type = c("seq", "div"))
view_all_palettes(type = "div", colourblind_friendly = TRUE)
```

Index

* datasets

PrettyColsPalettes, 4

colorblind_friendly, 2

colourblind_friendly, 3

discrete_scale, 5, 7, 9

prettycols, 3

PrettyColsPalettes, 4

scale_color_gradientn, 4

scale_color_pretty_c, 4

scale_color_pretty_d, 5

scale_color_pretty_div, 6

scale_colour_gradient2, 6, 8, 10

scale_colour_gradientn, 7

scale_colour_pretty_c, 6

scale_colour_pretty_d, 7

scale_colour_pretty_div, 8

scale_fill_gradientn, 9

scale_fill_pretty_c, 8

scale_fill_pretty_d, 9

scale_fill_pretty_div, 10

view_all_palettes, 10