

Package: ggauto (via r-universe)

October 21, 2026

Title Automatically Create and Style 'ggplot2' Charts

Version 0.0.2

Description Automatically choose an appropriate chart type based on the types and values in the data. Apply more accessible default styling and colours to 'ggplot2' charts.

License MIT + file LICENSE

Depends R (>= 4.1)

Imports dplyr, ggdist, ggforce, gghighlight, ggplot2, ggrepel, ggtext, glue, khroma, lemon, lubridate, rlang, scales, stringr

Suggests knitr, rmarkdown

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/Needs/website nrennie/nrenniepkgdown

URL <https://nrennie.rbind.io/ggauto/>

BugReports <https://github.com/nrennie/ggauto/issues>

VignetteBuilder knitr

Config/pak/sysreqs

libfontconfig1-dev libfreetype6-dev libicu-dev libjpeg-dev libpng-dev libxml2-dev libssl-dev

Repository <https://nrennie.r-universe.dev>

Date/Publication 2026-06-27 18:31:42 UTC

RemoteUrl <https://github.com/nrennie/ggauto>

RemoteRef HEAD

RemoteSha c3a8338fb847c281519bca3c1d12eba1678e0963

Contents

ggauto	2
Index	3

`ggauto`*Automated ggplot2 charts*

Description

Automatically create an appropriate 'ggplot2' chart type based on the classes of the provided variables.

Usage

```
ggauto(  
  data = NULL,  
  ...,  
  xlab = NULL,  
  ylab = NULL,  
  title = NULL,  
  subtitle = NULL,  
  caption = NULL,  
  base_size = 14,  
  base_family = "sans"  
)
```

Arguments

<code>data</code>	A data frame, or a bare vector when not using the pipe.
<code>...</code>	Unquoted column names to plot (e.g. <code>v1</code> , <code>v2</code>).
<code>xlab</code>	Label for the x-axis.
<code>ylab</code>	Label for the y-axis.
<code>title</code>	Optional plot title.
<code>subtitle</code>	Optional plot subtitle.
<code>caption</code>	Optional plot caption.
<code>base_size</code>	Base font size. Defaults to 14.
<code>base_family</code>	Base font family. Defaults to "sans".

Value

A ggplot2 plot object.

Examples

```
ggauto(mtcars$mpg)  
mtcars |> ggauto(mpg, wt)
```

Index

ggauto, [2](#)